

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 1 of 13

Clear Epoxy Hardener - Part B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Name: Clear Epoxy Hardener - Part B

Product code: 50112, 50112H, 50114, 50114H, 50132, 50240, 50240H



1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Not determined or not applicable.

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

1.3 Details of the manufacturer/supplier of the safety data sheet

Manufacturer:

North America

JB Weld Company, LLC
400 CMH Road
Sulpher Springs, TX 75482
903-885-7696
info@jbweld.com

Supplier:

European Union

JRP Distribution Ltd.
Unit 3 New Wharf Brighton Road
Shoreham by Sea, BN43 6RN

1.4 Emergency telephone number:

United Kingdom

CHEMTREC

1-703-527-3887

+(44)-870-8200418 (London)

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture:

Classification according to Regulation (EC) No. 1272/2008 (CLP):

Skin corrosion, category 1B

Skin sensitization, category 1

Eye irritation, category 2A

Chronic aquatic hazard, category 3

Hazard-determining components of labeling:

Poly(oxy(methyl-1,2-ethanediyl)), alpha-hydro-omega-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether

1-Piperazineethanamine

1,6-Hexanediamine, C,C,C-trimethyl-

Triethylenetetramine

Propylidynetrimethanol, propoxylated, reaction products with ammonia

N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)

3-aminopropyltriethoxysilane

2.2 Label elements

Hazard pictograms:



Signal word: Danger

Hazard statements:

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 2 of 13

Clear Epoxy Hardener - Part B

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash skin and eyes thoroughly after handling.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P310 Immediately call a POISON CENTER or doctor/physician.

P321 Specific treatment (see supplemental first aid instructions on this label).

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P362+P364 Take off contaminated clothing and wash it before reuse.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists get medical advice/attention

P405 Store locked up.

P501 Dispose of contents/container in accordance with local regulations.

2.3 Other hazards: None known

SECTION 3: Composition/information on ingredients

3.1 Substance: Not applicable.

3.2 Mixture:

Identification	Name	Classification according to Regulation (EC) No. 1272/2008 (CLP)	Weight %
CAS number: 72244-98-5	Poly(oxy(methyl-1,2-ethanediyl)), alpha-hydro-omega-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Skin Sens. 1; H317 Aquatic Chronic 3; H412	<90
CAS number: 112-24-3 EC number: 203-950-6	Triethylenetetramine	Acute Tox. 4; H312 Skin Sens. 1; H317 Skin Corr. 1B; H314 Aquatic Chronic 3; H412	<5
CAS number: 140-31-8 EC number: 205-411-0	1-Piperazineethanamine	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Sens. 1; H317 Skin Corr. 1B; H314 Aquatic Chronic 3; H412	<5
CAS number: 25620-58-0 EC number: 247-134-8	1,6-Hexanediamine, C,C,C-trimethyl-	Acute Tox. 4; H302 Skin Sens. 1; H317 Skin Corr. 1B; H314 Aquatic Chronic 3; H412	<5

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 3 of 13

Clear Epoxy Hardener - Part B

CAS number: 39423-51-3 EC number: 500-105-6	Propylidynetrimethanol, propoxylated, reaction products with ammonia	Acute Tox. 4; H302 Acute Tox. 4; H312 Eye Dam. 1; H318 Aquatic Chronic 2; H411	<2.1
CAS number: 100-51-6 EC number: 202-859-9	Benzyl Alcohol	Acute Tox. 4; H302 Acute Tox. 4; H332	<2
CAS number: 919-30-2 EC number: 213-048-4	3-aminopropyltriethoxysilane	Acute Tox. 4; H302 Skin Corr. 1B; H314	<2
CAS number: 3033-62-3 EC number: 221-220-5	N,N,N',N'-tetramethyl-2,2'- oxybis(ethylamine)	Acute Tox. 4; H302 Acute Tox. 3; H311 Acute Tox. 4; H332 Skin Corr. 1B; H314 Eye Dam. 1; H318	<0.9

Additional information: None

Full Text of H and EUH statements: See section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes:

Not determined or not available.

Following inhalation:

Loosen clothing as necessary and position individual in a comfortable position
Maintain an unobstructed airway
Get medical advice/attention if you feel unwell
Take precautions to ensure your own safety
Remove source of exposure or move person to fresh air and keep comfortable for breathing
Immediately call a POISON CONTROL CENTER or seek medical attention
If breathing has stopped, trained personnel should begin rescue breathing
Avoid mouth-to-mouth contact by using a barrier device
If the heart has stopped, immediately start cardiopulmonary resuscitation (CPR)

Following skin contact:

Rinse affected area with soap and water
If symptoms develop or persist, seek medical attention
Avoid direct contact and wear chemical protective clothing, if necessary
Immediately take off all contaminated clothing
Gently blot or brush away excess product
Rinse skin with lukewarm, gently flowing water until medical aid is available
Immediately call a POISON CONTROL CENTER or seek medical attention
Wash contaminated clothing before re-use or discard

Following eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes
If symptoms develop or persist, seek medical attention
Avoid direct contact and wear chemical protective gloves, if necessary
Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open
Remove contact lenses, if present and easy to do so
Continue rinsing until medical aid is available
Immediately call a POISON CONTROL CENTER or seek medical attention

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 4 of 13

Clear Epoxy Hardener - Part B

Following ingestion:

- Rinse mouth thoroughly
- Seek medical attention if irritation, discomfort, or vomiting persists
- Immediately call a POISON CONTROL CENTER or seek medical attention
- Do not induce vomiting and rinse mouth
- If vomiting occurs naturally, lie on your side, in the recovery position
- If breathing has stopped, trained personnel should begin rescue breathing
- Avoid mouth-to-mouth contact by using a barrier device
- If the heart has stopped, immediately start cardiopulmonary resuscitation (CPR)

4.2 Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not available.

Delayed symptoms and effects:

Not determined or not available.

4.3 Indication of any immediate medical attention and special treatment needed

Specific treatment:

Not determined or not available.

Notes for the doctor:

Not determined or not available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Use Water (fog only), dry chemical, chemical foam, carbon dioxide, or alcohol-resistant foam.

Unsuitable extinguishing media:

Not determined or not applicable.

5.2 Special hazards arising from the substance or mixture:

Thermal decomposition can lead to release of irritating gases and vapors.

5.3 Advice for firefighters

Personal protection equipment:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit.

Special precautions:

- Shut off sources of ignition.
- Carbon monoxide and carbon dioxide may form upon combustion.
- Heating causes a rise in pressure, risk of bursting and combustion.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

- Ensure adequate ventilation.
- Ensure air handling systems are operational.
- Wear protective eye wear, gloves and clothing.

6.2 Environmental precautions:

- Should not be released into the environment.
- Prevent from reaching drains, sewer or waterway.

6.3 Methods and material for containment and cleaning up:

- Wear protective eye wear, gloves and clothing.
- Use spark-proof tools and explosion-proof equipment.
- Absorb with non-combustible liquid-binding material (sand, diatomaceous earth (clay), acid binders, universal binders).
- Dispose of contents / container in accordance with local regulations.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 5 of 13

Clear Epoxy Hardener - Part B

6.4 Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Use only with adequate ventilation.

Avoid breathing mist or vapor.

Do not eat, drink, smoke or use personal products when handling chemical substances.

Take precautionary measures against electrostatic discharges.

Use only non-sparking tools.

7.2 Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.

Protect from freezing and physical damage.

Store in a cool, well-ventilated area.

Store away from all ignition sources (open flames, hot surfaces, direct sunlight, spark sources).

7.3 Specific end use(s):

Not determined or not applicable.

SECTION 8: Exposure controls/personal protection



8.1 Control parameters

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Finland	3-aminopropyltriethoxysilane	919-30-2	8-hour limit: 28 mg/m ³ (3 ppm)
	3-aminopropyltriethoxysilane	919-30-2	15-minute limit: 55 mg/m ³ (6 ppm)
	Benzyl Alcohol	100-51-6	8-hour limit: 10 ppm (45 mg/m ³)
Bulgaria	Benzyl Alcohol	100-51-6	TWA: 5.0 mg/m ³
Estonia	Triethylenetetramine	112-24-3	8-hour TWA: 1 ppm (6 mg/m ³)
	Triethylenetetramine	112-24-3	STEL: 12 mg/m ³
Belgium	N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	3033-62-3	8-hour TWA: 0.33 mg/m ³ (0.05 ppm)
	N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	3033-62-3	15-minute STEL: 1 mg/m ³ (0.15 ppm)
Czech Republic	Benzyl Alcohol	100-51-6	8-hour TWA: 40 mg/m ³
	Benzyl Alcohol	100-51-6	Ceiling limit (NPK-P): 80 mg/m ³
Lithuania	Triethylenetetramine	112-24-3	8-hour TWA: 6 mg/m ³ (1 ppm)
	Triethylenetetramine	112-24-3	15-minute STEL: 12 mg/m ³ (2 ppm)
	Benzyl Alcohol	100-51-6	8-hour TWA: 5 mg/m ³
Latvia	Benzyl Alcohol	100-51-6	8-hour TWA: 5 mg/m ³
Italy	N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	3033-62-3	15-min. STEL: 0.15 ppm

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 6 of 13

Clear Epoxy Hardener - Part B

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	3033-62-3	8-hour TWA: 0.05 ppm
Poland	Benzyl Alcohol	100-51-6	8-hour TWA (NDS): 240 mg/m ³
	Triethylenetetramine	112-24-3	8-hour TWA (NDS): 1 mg/m ³
	Triethylenetetramine	112-24-3	15-minute STEL (NDSCh): 3 mg/m ³
Portugal	N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	3033-62-3	8-Hour exposure limit: 0.05 ppm
	N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	3033-62-3	Short-term exposure limit: 0.15 ppm
Romania	Triethylenetetramine	112-24-3	8-hour TWA: 10 mg/m ³ (1.7 ppm)
	Triethylenetetramine	112-24-3	15-minute STEL: 20 mg/m ³ (3.3 ppm)
Sweden	Triethylenetetramine	112-24-3	Level Limit Value (NGV): 1 ppm (6 mg/m ³)
	Triethylenetetramine	112-24-3	Short Term Limit (KTV): 2 ppm (12 mg/m ³)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Derived No Effect Level (DNEL):

Not determined or not applicable.

Predicted No Effect Concentration (PNEC):

Not determined or not applicable.

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. Biological monitoring may also be appropriate for some substances.

8.2 Exposure controls

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

Use explosion-proof ventilation equipment.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

Environmental exposure controls:

Select controls based on a risk assessment of local conditions.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 7 of 13

Clear Epoxy Hardener - Part B

See section 6 for information on accidental release measures.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Clear liquid
Odor	Not available
Odor threshold	Not available
pH	Not available
Melting point/freezing point	Not available
Initial boiling point/range	Not available
Flash point (closed cup)	67°C (153°F)
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Upper flammability/explosive limit	Not available
Lower flammability/explosive limit	Not available
Vapor pressure	Not available
Vapor density	Not available
Density	1.127 g/cm ³
Relative density	Not available
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not available
Auto/Self-ignition temperature	Not available
Decomposition temperature	Not available
Dynamic viscosity	Not available
Kinematic viscosity	Not available
Explosive properties	Not available
Oxidizing properties	Not available

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity:

Does not react under normal conditions of use and storage.

10.2 Chemical stability:

Stable under normal conditions of use and storage.

10.3 Possibility of hazardous reactions:

None under normal conditions of use and storage.

10.4 Conditions to avoid:

None known.

10.5 Incompatible materials:

None known.

10.6 Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 8 of 13

Clear Epoxy Hardener - Part B

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Benzyl Alcohol	inhalation	LC50 Rat: 4.178 mg/L (4 hr)
	oral	LD50 Rabbit: 1,040 mg/kg
1-Piperazineethanamine	oral	LD50 - Chicken - 1,500 mg/kg
Propylidynetrimethanol, propoxylated, reaction products with ammonia	oral	LD50 - Rat - 550 mg/kg
	dermal	LD50 - Rat - > 1,000 mg/kg
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	oral	LD50 - Rat - 571 mg/kg
	inhalation	LC50 - Rat - 4.0 mg/L - 4 h (aerosol)
	dermal	LD50 - Rabbit - 750 mg/kg
3-aminopropyltriethoxysilane	oral	LD50 Rat: 1780 mg/kg

Skin corrosion/irritation

Assessment: Causes severe skin burns and eye damage

Product data:

No data available.

Substance data:

Name	Result
1-Piperazineethanamine	Corrosive to the skin.
1,6-Hexanediamine, C,C,C-trimethyl-	Causes skin burns
Triethylenetetramine	Causes severe skin burns and eye damage.
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Corrosive to the skin.
3-aminopropyltriethoxysilane	Causes severe skin burns and eye damage.

Serious eye damage/irritation

Assessment: Causes serious eye irritation

Product data:

No data available.

Substance data:

Name	Result
Propylidynetrimethanol, propoxylated, reaction products with ammonia	Corrosive to the eyes.
N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Corrosive effect on the eyes.

Respiratory or skin sensitization

Assessment: May cause an allergic skin reaction

Product data:

No data available.

Substance data:

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 9 of 13

Clear Epoxy Hardener - Part B

Name	Result
Poly(oxy(methyl-1,2-ethanediyl)), alpha-hydro-omega-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	May cause an allergic skin reaction.
1-Piperazineethanamine	Sensitization possible through skin contact.
1,6-Hexanediamine, C,C,C-trimethyl-	Sensitization possible through skin contact.
Triethylenetetramine	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

International Agency for Research on Cancer (IARC): None of the ingredients are listed.

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 10 of 13

Clear Epoxy Hardener - Part B

12.1 Toxicity

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Triethylenetetramine	LC50 - Daphnia magna (Water flea) - 33.9 mg/L - 48 h
Propylidynetrimethanol, propoxylated, reaction products with ammonia	EC50 - Pseudokirchnerella subcapitata - 4.4 mg/L - 72 h

Chronic (long-term) toxicity

Product data: No data available.

Substance data:

Name	Result
Poly(oxy(methyl-1,2-ethanediyl)), alpha-hydro-omega-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	NOEC - Daphnia magna (Water flea) - 3.5 mg/L - 21 d

12.2 Persistence and degradability

Product data: No data available.

Substance data: No data available.

12.3 Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

12.4 Mobility in soil

Product data: No data available.

Substance data: No data available.

12.5 Results of PBT and vPvB assessment

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

12.6 Other adverse effects: No data available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Relevant information:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

International Carriage of Dangerous Goods by Road/Rail (ADR/RID)

UN number	UN 2735
UN proper shipping name	Amines, Liquid, Corrosive, n.o.s. (Triethylenetetramine, 1-Piperazineethanamine)
UN transport hazard class(es)	8



Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 11 of 13

Clear Epoxy Hardener - Part B

Packing group	III
Environmental hazards	None
Special precautions for user	None

International Carriage of Dangerous Goods by Inland Waterways (ADN)

UN number	UN 2735
UN proper shipping name	Amines, Liquid, Corrosive, n.o.s. (Triethylenetetramine, 1-Piperazineethanamine)
UN transport hazard class(es)	8 
Packing group	III
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

UN number	UN 2735
UN proper shipping name	Amines, Liquid, Corrosive, n.o.s. (Triethylenetetramine, 1-Piperazineethanamine)
UN transport hazard class(es)	8 
Packing group	III
Environmental hazards	None
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	UN 2735
UN proper shipping name	Amines, Liquid, Corrosive, n.o.s. (Triethylenetetramine, 1-Piperazineethanamine)
UN transport hazard class(es)	8 
Packing group	III
Environmental hazards	None
Special precautions for user	None

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk Name	None
Ship type	None
Pollution category	None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

European regulations

Inventory listing (EINECS):

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 12 of 13

Clear Epoxy Hardener - Part B

72244-98-5	Poly(oxy(methyl-1,2-ethanediyl)), alpha-hydro-omega-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	Not Listed
100-51-6	Benzyl Alcohol	Listed
140-31-8	1-Piperazineethanamine	Listed
112-24-3	Triethylenetetramine	Listed
39423-51-3	Propylidynetrimethanol, propoxylated, reaction products with ammonia	Listed
3033-62-3	N,N,N',N'-tetramethyl-2,2'-oxybis(ethylamine)	Listed
919-30-2	3-aminopropyltriethoxysilane	Listed

REACH SVHC candidate list: None of the ingredients are listed.

REACH SVHC Authorizations: None of the ingredients are listed.

REACH Restriction: None of the ingredients are listed.

Water hazard class (WGK) (Product): Not determined.

Water hazard class (WGK) (Substance):

Ingredient Name	CAS	Class
Poly(oxy(methyl-1,2-ethanediyl)), alpha-hydro-omega-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptopropyl ether	72244-98-5	1
Benzyl Alcohol	100-51-6	1
1-Piperazineethanamine	140-31-8	2
Triethylenetetramine	112-24-3	2

Other regulations

Germany MAK: Benzyl Alcohol: 8-hour TWA: 5 ppm (22 mg/m³)

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

Indication of changes:

Not applicable.

Abbreviations and Acronyms: None

Classification procedure:

Classification according to Regulation (EC) No. 1272/2008 (CLP)	Method Used
Skin corrosion, category 1B	Calculation method
Skin sensitization, category 1	Calculation method
Eye irritation, category 2A	Calculation method
Chronic aquatic hazard, category 3	Calculation method

Summary of classification in section 3:

Skin Sens. 1; H317	Skin sensitization, category 1
Aquatic Chronic 3; H412	Chronic aquatic hazard, category 3
Acute Tox. 4; H312	Acute toxicity (dermal), category 4
Skin Corr. 1B; H314	Skin corrosion, category 1B
Acute Tox. 4; H302	Acute toxicity (oral), category 4
Eye Dam. 1; H318	Serious eye damage, category 1

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 01.18.2019

Page 13 of 13

Clear Epoxy Hardener - Part B

Aquatic Chronic 2; H411	Chronic aquatic hazard, category 2
Acute Tox. 4; H332	Acute toxicity (inhalation), category 4
Acute Tox. 3; H311	Acute toxicity (dermal), category 3

Summary of hazard statements in section 3:

H317	May cause an allergic skin reaction
H412	Harmful to aquatic life with long lasting effects
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H302	Harmful if swallowed
H318	Causes serious eye damage
H411	Toxic to aquatic life with long lasting effects
H332	Harmful if inhaled
H311	Toxic in contact with skin

Disclaimer:

This product has been classified in accordance with EC No. 1272/2008 (CLP) and EC No. 1907/2006 (REACH). The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 01.18.2019

End of Safety Data Sheet